



SERIES 1358 & 1358-C

NON-ROTATING DIVERTER

The Washington Series 1358 & 1358-C Non-Rotating Diverters are ideal for use on Top Drive Rigs or Work Over Rigs where drill pipe is to be rotated inside stripper rubber. Whether drilling oil, gas, water or monitor wells, the 1358 bolt down style or the 1358-C clamp down style is a low profile diverter that is lightweight, compact and easy to install. Using air/ water or mud as a circulating medium, it is a cost effective solution to safely diverting all drill cuttings away from the rig and personnel or into a container for disposal, keeping clean up cost to a minimum.

The diverter can be manufactured with any desired inlet or outlet flange, or can be manufactured to thread onto casing. To be used with 4010 stripper rubber. Will handle from 2" to 8" drill pipe.



Nominal Flange Size	A	C	F	Outlet
7 1/16" - 3000	18 11/16"	8 1/2"	7 1/16"	Per request
7 1/16" - 5000	19 1/8"	8 7/8"	7 1/16"	Per request
9" - 3000	18 5/16"	8 1/2"	9"	Per request
9" - 5000	18 7/16"	8 5/8"	9"	Per request
11" - 3000	16 7/16"	7 1/8"	11 1/8"	Per request
11" - 5000	16 11/16"	7 3/8"	11 1/8"	Per request
13 5/8" - 3000	16 9/16"	7 1/4"	12 3/8"	Per request
13 5/8" - 5000	16 9/16"	7 1/4"	12 3/8"	Per request

WHEN ORDERING, PLEASE SPECIFY:

1. Model number
2. Inlet flange size
3. Outlet flange size
4. Kelly size and shape
5. Drill pipe & tool joint OD
6. Drilling environment
7. High temperature, if applicable.

All air bowls can be fitted with female collared or flanged outlets at your request.

All air bowls can be double drilled at your request.

Washington Rotating Control Heads, Inc.
 P: 724.228.8889 | F: 724.228.8912
 63 Springfield Avenue
 Washington, PA 15301
www.washingtonrotating.com

Our test pressures have been established through controlled test procedures. As a result of the ever-changing environment of well drilling operations along with wear and tear on equipment, which erodes longevity and safe operating parameters, Washington Rotating Control Heads, Inc., its Business Units, Agents and Affiliates make no warranty either expressed or implied on the test pressures contained herein. Washington Rotating Control Heads, Inc. does not under any circumstances recommend that its rotating control devices be used as primary blow out prevention equipment.

API Specification Q1 - Registration No. Q1-2651

ISO 9001:2015-APIQR Registration No. 2775