



SERIES 2300-L

ROTATING CONTROL DEVICE

The Washington Series 2300-L is a low profile Rotating Control Device designed for top drive rigs or workover rigs. The frictional engagement between the drill string and stripper rubber rotates the Control Device with the drill string sealing off the well bore continuously while diverting all cuttings and debris. Whether you are drilling gas, oil, or geothermal wells, Washington Rotating can accommodate all your diverter needs.

This unit is designed to be used with our 4010-V stripper rubber and will seal off all drill from 2"-8" OD. This unit can also be fitted with a non-rotating assembly (call for details).



WHEN ORDERING, PLEASE SPECIFY:

1. Model number
2. Inlet flange size
3. Outlet flange size
4. Kelly size and shape
5. Drill pipe & tool joint OD
6. Drilling environment
7. High temperature, if applicable.

All air bowls can be fitted with flanged outlets per your request.

All air bowls can be double drilled at your request.

MODEL 2300 SPECIFICATIONS	
Maximum R.P.M. (Intermittent)	300 RPM
Stripper Rubber Mounting	Bolted
RCDs	Available in standard oiled

Nominal Flange Size	A	B	C	RCD Bore D	Bowl Bore F	Outlet Flange
7 1/16" - 3000	26 7/8"	21"	11 5/8"	8 1/8"	17 1/16"	Per request
7 1/16" - 5000	26 7/8"	21"	11 5/8"	8 1/8"	17 1/16"	Per request
9" - 3000	26 7/8"	20"	11 5/8"	8 1/8"	9"	Per request
9" - 5000	26 7/8"	20"	11 5/8"	8 1/8"	9"	Per request
11" - 3000	21 7/8"	16"	6 5/8"	8 1/8"	11 1/8"	Per request
11" - 5000	21 7/8"	16"	6 5/8"	8 1/8"	11 1/8"	Per request
13 5/8" - 3000	21 7/8"	16"	7 1/8"	8 1/8"	13 5/8"	Per request
13 5/8" - 5000	21 7/8"	16"	7 1/8"	8 1/8"	13 5/8"	Per request

Washington Rotating Control Heads, Inc.
 P: 724.228.8889 | F: 724.228.8912
 63 Springfield Avenue
 Washington, PA 15301
www.washingtonrotating.com

Our test pressures have been established through controlled test procedures. As a result of the ever-changing environment of well drilling operations along with wear and tear on equipment, which erodes longevity and safe operating parameters, Washington Rotating Control Heads, Inc., its Business Units, Agents and Affiliates make no warranty either expressed or implied on the test pressures contained herein. Washington Rotating Control Heads, Inc. does not under any circumstances recommend that its rotating control devices be used as primary blow out prevention equipment.

API Specification Q1 - Registration No. Q1-2651

ISO 9001:2015-APIQR Registration No. 2775